



TEKNISK INFORMATION

BSW Gevind

| Nominal Ø i tommer | Gevindstigning i " | Gevind Ø mm | Nominal Ø i tommer | Gevindstigning i " | Gevind Ø mm |
|--------------------|--------------------|-------------|--------------------|--------------------|-------------|
| 1/16 | 60 | 1,587 | 7/8 | 9 | 22,226 |
| 3/32 | 48 | 2,381 | 1 | 8 | 25,401 |
| 1/8 | 40 | 3,175 | 1 1/8 | 7 | 28,576 |
| 5/32 | 32 | 3,969 | 1 1/4 | 7 | 31,751 |
| 3/16 | 24 | 4,762 | 1 3/8 | 6 | 34,926 |
| 7/32 | 24 | 5,556 | 1 1/2 | 6 | 38,101 |
| 1/4 | 20 | 6,350 | 1 5/8 | 5 | 41,227 |
| 5/16 | 18 | 7,938 | 1 3/4 | 5 | 44,452 |
| 3/8 | 16 | 9,525 | 1 7/8 | 4,5 | 47,627 |
| 7/16 | 14 | 11,113 | 2 | 4,5 | 50,802 |
| 1/2 | 12 | 12,700 | 2 1/4 | 4 | 57,152 |
| 9/16 | 12 | 14,288 | 2 1/2 | 4 | 63,502 |
| 5/8 | 11 | 15,876 | 2 3/4 | 3,5 | 69,853 |
| 3/4 | 10 | 19,051 | 3 | 3,5 | 76,203 |

BSF Gevind

| Nominal Ø i tommer | Gevindstigning i " | Gevind Ø mm | Nominal Ø i tommer | Gevindstigning i " | Gevind Ø mm |
|--------------------|--------------------|-------------|--------------------|--------------------|-------------|
| 3/16 | 32 | 4,762 | 13/16 | 12 | 20,638 |
| 7/32 | 28 | 5,556 | 7/8 | 11 | 22,226 |
| 1/4 | 26 | 6,350 | 15/16 | 11 | 23,813 |
| 5/16 | 22 | 7,938 | 1 | 10 | 25,401 |
| 3/8 | 20 | 9,525 | 1 1/8 | 9 | 28,576 |
| 7/16 | 18 | 11,113 | 1 1/4 | 9 | 31,751 |
| 1/2 | 16 | 12,700 | 1 3/8 | 8 | 34,926 |
| 9/16 | 16 | 14,288 | 1 1/2 | 8 | 38,101 |
| 5/8 | 14 | 15,876 | 1 5/8 | 8 | 41,227 |
| 11/16 | 14 | 17,463 | 1 3/4 | 7 | 44,452 |
| 3/4 | 12 | 19,051 | 2 | 7 | 50,802 |

UNC- og UN-Gevind

| Nominal Ø i tommer | Gevindstigning i " UNC | Gevindstigning i " UNF | Gevindstigning i " UNEF | Gevind Ø mm |
|-----------------------|---------------------------|---------------------------|----------------------------|----------------|
| 0 | - | 80 | - | 1,520 |
| 1 | 64 | 72 | - | 1,850 |
| 2 | 56 | 72 | - | 1,850 |
| 3 | 48 | 56 | - | 2,520 |
| 4 | 40 | 48 | - | 2,850 |
| 5 | 40 | 44 | - | 3,180 |
| 6 | 32 | 40 | - | 3,510 |
| 8 | 32 | 36 | - | 4,170 |
| 10 | 24 | 32 | - | 4,830 |
| 12 | 24 | 28 | 32 | 5,490 |
| 1/4 | 20 | 28 | 32 | 6,350 |
| 5/16 | 18 | 24 | 32 | 7,938 |
| 3/8 | 16 | 24 | 32 | 9,525 |
| 7/16 | 14 | 20 | 28 | 11,113 |
| 1/2 | 13 | 20 | 28 | 12,700 |
| 9/16 | 12 | 18 | 24 | 14,288 |
| 5/8 | 11 | 18 | 24 | 15,876 |
| 11/16 | - | - | 24 | 17,463 |
| 3/4 | 10 | 16 | 20 | 19,051 |
| 13/16 | - | - | 20 | 20,638 |
| 7/8 | 9 | 14 | 20 | 22,226 |
| 15/16 | - | - | 20 | 23,813 |
| 1 | 8 | 12 | 20 | 25,401 |
| 1/16 | - | - | 18 | 26,988 |
| 1 1/8 | 7 | 12 | 18 | 28,576 |
| 1 3/16 | - | - | 18 | 30,163 |
| 1 1/4 | 7 | 12 | 18 | 31,751 |
| 1 5/16 | - | - | 18 | 33,338 |
| 1 3/8 | 6 | 12 | 18 | 34,926 |
| 1 7/16 | - | - | 18 | 36,512 |
| 1 1/2 | 6 | 12 | 18 | 38,101 |
| 1 5/8 | 5 | - | 18 | 41,277 |
| 1 3/4 | 5 | - | 18 | 44,452 |
| 1 7/8 | 4,5 | - | 18 | 47,627 |
| 2 | 4,5 | - | 18 | 50,802 |
| 2 1/4 | 4,5 | - | - | 57,152 |
| 2 1/2 | 4 | - | - | 63,502 |
| 2 3/4 | 4 | - | - | 69,853 |
| 3 | 4 | - | - | 76,203 |

Rørgvind DIN ISO 228

| Nominal Ø i tommer | Gevindstigning i " | Gevind Ø mm | Nominal Ø i tommer | Gevindstigning i " | Gevind Ø mm |
|--------------------|--------------------|-------------|--------------------|--------------------|-------------|
| G 1/8 | 28 | 9,728 | G 1 1/2 | 11 | 47,803 |
| G 1/4 | 19 | 13,157 | G 1 3/4 | 11 | 53,746 |
| G 3/8 | 19 | 16,662 | G 2 | 11 | 59,614 |
| G 1/2 | 14 | 20,955 | G 2 1/4 | 11 | 65,710 |
| G 5/8 | 14 | 22,911 | G 2 1/2 | 11 | 75,184 |
| G 3/4 | 14 | 26,441 | G 2 3/4 | 11 | 81,534 |
| G 7/8 | 14 | 30,201 | G 3 | 11 | 87,884 |
| G 1 | 11 | 33,249 | G 3 1/4 | 11 | 93,980 |
| G 1 1/8 | 11 | 37,897 | G 3 1/2 | 11 | 100,330 |
| G 1 1/4 | 11 | 41,910 | G 3 3/4 | 11 | 106,680 |
| G 1 3/8 | 11 | 44,323 | G 4 | 11 | 113,030 |

Panzer Gevind DIN 40430 PG

| Nominal Ø i tommer | Gevindstigning i " | Gevind Ø mm |
|--------------------|--------------------|-------------|
| PG 7 | 20 | 12,500 |
| PG 9 | 18 | 15,200 |
| PG 11 | 18 | 18,600 |
| PG 13,5 | 18 | 20,400 |
| PG 16 | 18 | 22,500 |
| PG 21 | 16 | 28,300 |
| PG 29 | 16 | 37,000 |
| PG 36 | 16 | 47,000 |
| PG 42 | 16 | 54,000 |
| PG 48 | 16 | 59,500 |

SNITTAPPE
ALT I GEVINDVÆRKTØJER

